

<b>Technical data</b>	
<b>Total thickness</b>	7.5 mm
<b>Thickness of the useful layer</b>	2 mm
<b>Basis weight</b>	11 kg/m <sup>2</sup>
<b>Format tiles</b>	615 mm x 615 mm (effective area 595 mm x 595 mm)
<b>Hardness</b>	95 Shore A
<b>European classification</b>	34-43
<b>Walk-in loading</b>	<2kV
<b>Surface finish</b>	xr™-PUR coating
<b>Sliding resistance</b>	DS / R10
<b>Fire behavior</b>	B <sub>fl</sub> -s1
<b>Light fastness</b>	Stage 6
<b>Dimensional stability</b>	≤ 0,15
<b>Residual impression</b>	≤ 0,10
<b>Stair castor stress</b>	suitable
<b>Floor heating (warm water)</b>	Up to max. 30°C surface temperature suitable
<b>VOC-emissions</b>	Certified
<b>Use class</b>	Heavy and light commercial vehicle
<b>Operating class</b>	23-33-42
<b>Backside</b>	Drainage knobs
<b>Material</b>	Fiberglass reinforced PVC
<b>Impact sound improvement measure</b>	9 dB

## Environment friendly

- 100% recyclable (at the end of the useful life, we can pick up the tiles and recycle them)

- Made in Europa

